

Banner Vinyl matt 375 µm

Tetenal article numbers:

130907 (61.0 cm × 15 m) 130908 (106.7 cm × 15 m)

Product description:

The product Banner Vinyl matt 375 μm is a waterproof, heavy duty and flexible PVC banner material that has a finely structured surface of polyester fabric with a vinyl coating. Using the Banner Vinyl matt 375 μm material it is possible to achieve sharp, high contrast and high-resolution images. It is the perfect material for display advertisements both indoors and outdoors.

Product characteristics:

This highly tear-resistant banner material allows waterproof prints to be made using pigment-based inks. The result of weathering tests has shown that the material will last for approx. 3 months outdoors under central European climatic conditions. This banner material can be sewn and fitted with eyelets.

Fields of application:

Short-life advertisements indoors and outdoors, pop-up and banner displays, perimeter advertising, tensioned banners, signage, exhibition applications etc.

Notes on use:

Please store the material vertically in its original packaging (cardboard carton and polyethylene bag). The material should be used within 6 months of delivery at the most. When using

large format printers the automatic cutting unit must remain turned off in order to avoid premature wear of the cutting blade and prevent defects from occurring. To avoid fingerprints and marking of the film during handling, we recommend that cotton gloves are worn. The material should not be folded. The printing will only become completely waterproof once the ink has fully dried. It is recommended that the prints are first allowed to dry out for approx. 12 – 24 hours in the open before they are exposed to damp conditions.

Recommended printers:

EPSON Stylus Pro Series 7600 / 7800 / 7880 / 7890 / 7900 / 9800 / 9880 / 9890 / 9900

Canon image Prograf Series 8000 / 9000 / 6100 / 8100 / 9100 / 6200 / 6300 / 6350 / 8300

Further printers upon request.

Recommended storage conditions:

Temperature 10-30 °C Rel. humidity 35-65 %

Technical specifications:

Weight 400 g/m²
Surface matt
Colour white
Thickness 375 µm
Fire resistant no

Gloss (60°) 2.2 gloss units

Whiteness index (CIE): 98

