

Easy Tack Film 220 g

Tetenal Article Numbers:

132720 (61.0 cm x 30 m)

Product Description:

Easy Tack Film 220 g is a matt-coated and tear-resistant polypropylene film with a particularly low-tack adhesive.

The film has a paper-like feel and is suitable for a wide range of applications thanks to the easy tack adhesive, which is simple to both attach and remove. Easy tack adhesive enables easy, 100% bubble-free application, as well as ensuring that no residues are left behind on glass or many other surfaces.

Product Properties:

The Easy Tack Film coating features a high degree of whiteness, which, in combination with a high level of possible colour saturation, ensures a wide colour gamut. Prints feature a very good colour saturation and image definition.

In combination with pigmented inks, the water-resistant film achieves optimum durability for outdoor applications.

The Easy Tack Film 220 g inkjet coating is compatible with most water-based pigmented or dye-based inks.

The durable and flexible base is also very well suited to slightly uneven surfaces.

Applications:

Floor advertising, short-term indoor advertisements, indoor signs, outdoor signs, trade fair applications, billboard advertising, general outdoor advertising etc.

Applications Notes:

Please store the material in the original packaging (box & PE sack). When using large-format printers, the automatic cutting device must remain switched off to prevent excessive wear on the cutter or defects.

To prevent fingerprints and dirt when working with the film, we recommend wearing cotton gloves.

Prints are only guaranteed to be fully water-resistant once inks are completely dried. It is recommendable to dry prints in the open for approximately 12-24 hours before exposing them to dampness.

Please check the adhesiveness of the easy tack adhesive on a variety of surfaces prior to application.

Printer Compatibility:

EPSON Stylus Pro Series 7600 / 7800 / 7880 / 7890 / 7900 / 9600 / 9800 / 9880 / 9890 / 9900

Canon image Prograf Series 8000 / 9000 / 6100 / 8100 / 9100 / 6200 / 6300 / 6350 / 8300

HP DesignJet Z Series 2100 / 3100 / 6100 / 3200 / 5200 / 6200

Further printer recommendations on demand.

Recommended Storage Conditions:

Temperature	10-30 °C
Rel. air humidity	35-65 %

Technical Specifications:

Weight	220 g/m ²
Finish	matt
Colour	white
Material Thickness	325 µm
Core diameter	3 inches
Flame retardant	no
Gloss (60°)	2.5 gloss units
Colour Location	L=98.3 a=1.6 b=5.9