

## Wallpaper 170 g

### Tetenal Article Numbers:

132710 (61.0 cm x 30.5 m)

### Product Description:

The Wallpaper 170 g material features a high-quality inkjet coating, which enables a wide colour gamut and excellent colour rendering. This fleece wallpaper is very well suited to interior decoration. The product can cover small holes in walls and features a high degree of dimensional stability and wet strength. Wallpaper 170 g is easy to apply using a fleece wallpaper paste.

### Product Properties:

Thanks to the special structure of Wallpaper 170 g, ink is absorbed particularly quickly and dries so as to be smudge-proof immediately. The product may therefore be used very soon after printing.

The material features a smooth surface and a high degree of opacity. This product is suitable for short-term use outdoors and can be used without any protective varnish or laminate. The material is easy to remove and PVC-free. Pigmented inks are fixed on the surface so as to be water-resistant. Spray water may leave behind slight light/dark shadowing on the surface.

### Applications:

Personalised/individualised wallpapers, interior decoration.

### Applications Notes:

The material is shrink-resistant and may therefore be printed from edge to edge, without a margin. If marginless printing is not possible, the white edges should be cut off prior to pasting. Recommended pastes are those for fleece materials, in particular Henkel Metylan Direct, Henkel Metylan Spezial and Henkel Metylan Ovalit T.

Paste should always be applied to the wall, not the wallpaper. For sufficient protection, liquid lamination with varnishes (Drytack, Clearcoat) is recommended.

Please always store the material upright in the original packaging (box & PE sack).

To avoid scratches and dirt when working with the product, we recommend wearing cotton gloves. P

rints are only guaranteed to be fully water-resistant once inks are completely dried.

### Printer Compatibility:

EPSON Stylus Pro Series 7600 / 7800 / 7880 / 7890 / 7900 / 9600 / 9800 / 9880 / 9890 / 9900

Canon image Prograf Series 8000 / 9000 / 6100 / 8100 / 9100 / 6200 / 6300 / 6350 / 8300

HP DesignJet Z Series 2100 / 3100 / 6100 / 3200 / 5200 / 6200

Further printer recommendations on demand.

### Recommended Storage Conditions:

Temperature 10-30 °C

Rel. air humidity 35-65 %

### Technical Specifications:

Weight 170 g/m<sup>2</sup>

Finish matt

Colour white

Material Thickness 310 µm

Flame retardant no

Opacity > 92%

Degree of whiteness (CIE) 105

Gloss (85°) 1.4 gloss units

Colour Location L=96 a=0 b=-3