

Window Graphic Film 210 µm

Tetenal article numbers:

130909 (61.0 cm × 20 m)

130910 (106.7 cm × 20 m)

Product description:

This matt, translucent and self-adhesive inkjet polyester film is highly suitable for graphic art applications as a result of its partial transparency. This film has been developed especially for display window advertising. Thanks to the reduced bond strength of the adhesive the film can easily be applied to all types of smooth surface. It can also be removed again without leaving residues. Using the Window Graphic Film 210 µm it is possible to achieve sharp, high contrast images that achieve the perfect effect when backlit. This is the ideal solution for image presentations.

Product characteristics:

Translucent Window Graphic Film coated on one side with a matt white surface. High printing resolutions and vibrant colours can be achieved thanks to the instant-dry and scratchproof surface. The Window Graphic Film 210µm exhibits excellent dimensional stability and is therefore suitable for lamination. This self-adhesive polyester film is optimised for use in window displays.

Fields of application:

Lightbox displays/city light posters, window displays, image presentations, exhibition applications, high quality presentations, automotive use, architecture.

Notes on use:

The printed side is always on the outside of the roll. The printed side is also the display side.

For use in window displays the picture can be cut to shape using a large format cutter.

The product must not be applied while it is still wet and the side that takes the adhesive must not be cleaned with cleaning agents that contain silicon. Materials other than window glass must first be tested for their suitability. If the printed film is likely to come into contact with water, then we recommend that it is laminated. The adhesive is not water-resistant. To avoid finger-prints and marking of the film during handling, we recommend that cotton gloves are worn.

Recommended printers:

EPSON Stylus Pro Series 7600 / 7800 / 7880 / 7890 / 7900 / 9600 / 9800 / 9880 / 9890 / 9900

Canon image Prograf Series 8000 / 9000 / 6100 / 8100 / 9100 / 6200 / 6300 / 6350 / 8300

Further printers upon request.

Recommended storage conditions:

Temperature 10 - 30 °C

Rel. humidity 35 - 65 %

Technical specifications:

Weight	210 g/m²
Surface	matt, translucent film
Colour	white
Thickness	180 µm
Fire resistant	no
Gloss (60°)	2.3 gloss units